## (19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 14 July 2005 (14.07.2005)

**PCT** 

## (10) International Publication Number WO 2005/064225 A1

(51) International Patent Classification<sup>7</sup>: F16M 11/12, 11/18, G01R 35/00

(21) International Application Number:

PCT/EP2003/014965

(22) International Filing Date:

30 December 2003 (30.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): EU-ROPEAN ORGANIZATION FOR NUCLEAR RE-SEARCH [CH/CH]; CERN, CH-1211 Genf 23 (CH).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): BERGSMA, Felix [FR/FR]; 1, Résidence des Genevrays, F-01630 Peron (FR).
- (74) Agent: WEBER-BRULS, Dorothée; Boehmert & Boehmert, Hollerallee 32, 28209 Bremen (DE).


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SAMPLE DEVICE WITH TURNTABLE



(57) Abstract: The invention refers to a sample device to be inserted inside an external tube, having a substantially circular cross-section, and carrying a substantially circular plate as part of a turntable (4) to be rotated within the external tube (3) around two substantially othogonal axes. Two substantially coaxial tubes (3, 2), with the turntable being supported by the outer tube (3), and two meshing gears (30, 20), with the first gear (20) being connected to the inner tube (2) and the second gear (30) being connected to the turntable (4), and/or a special cable guide (5) being connected with its first end with the turntable (4) and its second end, being substantially perpendicular to the first end, with the sup-porting means, with the inner tube (2), the outer tube (3) and/or the cable guide (5) being connected with a driving unit, are provided for maximizing the surface of the plate to be rotated within the external tube.

| 1 V 3CCV30/3000